

## Sage Series C38/P38 Point Source

## In-wall/On-wall/Free-standing - Horizontal & Vertical

The C38 & P38 are not line source speakers, but is instead a point source loudspeaker. The vast majority of loudspeakers available in the world are point sources, meaning that they radiate their sonic energy outward in an expanding sphere, as though from a point in space. The Horizontal C38 can be used in in-wall (C38i), on-wall (C38m) or free-standing (C38) applications. And for Vertical applications the P38 can be used in in-wall (P38i), and on-wall (P38m). They both share the same driver technology, and are timbre matched and can be combined with other Sage Series in-wall, on-wall and freestanding models as desired for the specific installation. All versions are constructed entirely from aircraft grade aluminum. Though they look quite similar, the MTM tweeter is rotated 90 degrees for optimal dispersion. Four of the same high operating pressure 6-inch woofers used throughout Sage Series models mate with a unique MTM Planar Magnetic Driver array for the midrange and treble. The MTM array provides the same level of transparency, detail, and instantaneous dynamics as the 24-inch Planar Magnetic driver used in the L75, L100, and L150 (in multiples), but is a much smaller package optimized for the space requirements

As with most Sage Series products the use of an SC-2 or SC-3 is required for the necessary DSP and outboard electronic crossovers.

associated with the C38 & P38 and other more compact Sage Series models.

## **Specifications:**

- Frequency Response = 40Hz 20 kHz +/-2dB
- Sensitivity = 90 dB/1w/1m
- Planar Impedance = 3 ohms
- Woofer Column Impedance = 3 ohms
- Amplifier Channels Required = 2
- Dimensions = See Drawing PDF or DWG File



C38m pictured

P38i pictured