

Sage Series P48 Point Source

Free-standing

The P48 shares much in common with the P38, except that its design was specifically targeted for freestanding applications. It is not available in in-wall or on-wall versions. The P48 is not a line source like the L75 and L150i, but is instead a point source loudspeaker. The vast majority of loudspeakers available in the world are point sources, meaning that they radiate their sonic energy outward in an expanding sphere, as though from a point in space. The P48 is available in a freestanding version only, and sharing the same driver technology, it is timbre matched and can be

combined with other Sage Series in-wall, on-wall and freestanding models as is desired for the specific installation. Slim and elegant in design, the P48 blends nicely into a variety of décors where traditional loudspeakers might otherwise intrude excessively on the room's appearance. Constructed entirely from machined and extruded aircraft grade aluminum, the clear anodized interlocking trim bezels and matte charcoal colored cabinet convey an exquisite balance of industrial design and build quality unique among consumer loudspeakers.

As with most Sage Series products the use of an SC-2 or SC-3 is required for the necessary DSP and outboard electronic crossovers.

Specifications:

- Frequency Response = 40Hz 20 kHz +/-2dB
- Sensitivity = 90 dB/1w/1m
- Planar Impedance = 3 ohms
- Woofer Column Impedance = 3 ohms
- Amplifier Channels Required = 2
- Dimensions = See Drawing PDF or DWG File



All specifications are subject to change at any time in order to improve the product.