



SC-2 & SC-3 System Controllers

Second Generation System Controllers - The SC-2 and SC-3 provides fully calibrated hi-resolution audio for both home theater and multi-room applications.

Specifications

- SC-2: 8 channel in to 16 channel out (16 Dirac output channels) (2RU)
- SC-3: 16 channel in to 32 channel out (16 Dirac output channels) (3RU)
- All balanced analog XLR
- 24-bit 96kHz internal processing with a signal-to-noise ratio of -110 dB
- Setup via Ethernet and IP-based HTML page

Features

- Dirac Live Room Correction Suite™ with multi-zone capability
- Programming via Ethernet connection with browser-based configuration
- Expert Mode: For an additional layer of live tuning features
- Model-specific Wisdom Audio speaker crossover and PEQ profiles included
- Fully adjustable active crossovers, peaking filters, and delays
- 4-preset slots to store complete and independent calibrations with recall ability via RS-232 using AMX, Control4, Crestron, Savant, and other control platforms
- Up to 16 zones can be independently calibrated for superior performance for distributed music systems, and or full blown multichannel theater projects



All specifications are subject to change at any time in order to improve the product.

Wisdom Audio | 1572 College Parkway, Suite 164 | Carson City, NV 89706 | 775-887-8850 | fax 775-887-8820 | www.wisdomaudio.com | information@wisdomaudio.com
© 2017 Wisdom Audio Corporation. All rights reserved. Wisdom and the Wisdom logo are registered trademarks of Wisdom Audio.